

Non-contact temperature measurement of thin-film plastic materials from 35 °C to 600 °C (95 °F to 1112 °F)



Features:

- Miniaturized infrared thermometer with a spectral range of 3.43 µm for precise temperature measurements of thin-film plastic materials like PE, PP, PS
- Two-piece design with easy accessible programming keys and LCD backlit display
- Built-in USB interface for simple sensor setup via mobile phone or PC
- Selectable analog outputs: 0/4 – 20 mA, 0 – 5 V, 0 – 10 V, thermocouple type K
- Optional EtherNet/IP, Profinet, Ethernet TCP/IP / Modbus TCP, Modbus RTU, RS485, RS232 interface or relay outputs (2 x optically isolated)
- Easy and flexible exchange of sensing heads

General specifications

Environmental rating	IP 65 (NEMA-4)
Operating temperature range ¹⁾	–20 °C ... 85 °C (–4 °F ... 185 °F) (sensing head) –20 °C ... 85 °C (–4 °F ... 185 °F) (electronics)
Storage temperature	–40 °C ... 85 °C (–40 °F ... 185 °F) (sensing head) –40 °C ... 85 °C (–40 °F ... 185 °F) (electronics)
Operating air humidity range	10–95 %, non condensing
Vibration (sensor)	IEC 60068-2-6 (sinus shaped) IEC 60068-2-64 (broadband noise)
Shock (sensor)	IEC 60068-2-27 (25G and 50G)
Weight	200 g (7.05 oz) (sensing head incl. massive housing) / 420 g (14.82 oz) (electronics)

Electrical Specifications

Output / analog (2x)	0 / 4 – 20 mA, 0 – 5 / 10 V, thermocouple K, alarm
Output / alarm	24 V / 50 mA (open collector)
Relay outputs (optional)	2 x 60 V DC / 42 V AC _{RMS} ; 0.4 A; optically isolated
Digital Interfaces	built-in USB-interface, Optional: EtherNet/IP, Profinet, EtherCAT Ethernet TCP/IP / Modbus TCP, Modbus RTU, RS485, RS232 or relay outputs (2 x optically isolated)
Output impedances	mA max. 500 Ω (with 8 – 36 V DC) mV min. 100 kΩ load impedance
I/O Pins (3x)	flexible programming as in- or output: external emissivity adjustment, ambient temperature compensation, uncommitted value, trigger (reset of hold functions), alarm output (open collector 24 V / 50 mA)
Cable length	3 m (9.84 ft) (standard), 8 m (26.25 ft), 15 m (49.21 ft)
Power supply	8 - 30 V DC / 1.2W

Measurement specifications

Measuring Temperature range (scalable via programming keys or software / App) ⁸⁾	35 °C ... 600 °C (95 °F ... 1112 °F)
Spectral range	3.43 µm
Optical resolution (90% energy)	15:1
Measurement uncertainty ^{2), 3), 4), 7), 9)}	±2.5 °C or ±1 % (±4.5 °F or ±1 %)
Repeatability ^{4), 5), 6), 7)}	±0.25 K
Temperature resolution (display)	0.1 K
NETD (typically) ^{4), 5), 6), 7)}	90 mK
Response time (90% energy)	15 ms
Emissivity / Gain (adjustable via programming keys or software / App)	0.05–1.100
Transmissivity / Gain (adjustable via programming keys or software / App)	0.05–1.100
Signal processing (parameter adjustable via programming keys or software / App)	Peak hold, valley hold, average; extended hold functions with threshold and hysteresis
Software / App	Optris CompactPlus Connect / IR Mobile App

¹⁾ The LCD display capacity may be limited at ambient temperatures below 0 °C (32 °F)

²⁾ whichever is greater

³⁾ Response time = 1 s (90%)

⁴⁾ ε = 1.000

⁵⁾ T_{obj} = 100 °C (212 °F)

⁶⁾ Response time = 100 ms (90%)

⁷⁾ at ambient temp. (23 ± 5) °C (73.4 ± 9 °F)

⁸⁾ T_{obj} > T_{Head} + 10 °C (18 °F)

⁹⁾ specifications are valid for temperatures above 50 °C (122 °F)

Optical specifications - Standard Focus (SF)




D:S	Optical values											
	0	100	200	300	400	500	600	700	800	900	1000	Distance in mm (ft)
10:1	6.5 (0.26)	11.5 (0.45)	16.6 (0.65)	21.6 (0.85)	26.7 (1.05)	35.0 (1.38)	43.3 (1.7)	51.5 (2.03)	59.8 (2.35)	68.1 (2.68)	76.4 (3.01)	Spotsize in mm (ft)




More optical data: <https://optris.com/us/optris-calculator>

Dimensions (in mm)

Electronics



Sensing head
with Massive housing



Software / App



<https://optris.com/us/software/>

